

A-20 is a woven UV stabilized HDPE scrim with a polyethylene coating on both sides.

**PHYSICAL PROPERTIES AND TYPICAL VALUES**

PROPERTY	ASTM TEST METHOD	U.S. VALUE	METRIC VALUE
Weight	D-2103	29 LB/1000 FT <sup>2</sup>	14.2 KG/100 M <sup>2</sup>
Thickness	D-2103	6.75 MIL	0.171 MM
Tensile Grab Strength	D-751	180 LBS	800 N
Tongue Tear	D-751 B	50 LBF	222 N
Trapezoidal Tear	D-4533	33 LBF	147 N

**AVAILABLE COLORS**

Clear or Black/White

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, expressed or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

©2006 REEF INDUSTRIES, INC. Armorlon is a registered trademark of Reef Industries, Inc. 09-06

**TOLLFREE 1.800.231.6074**

9209 Alameda Genoa Rd. • Houston, Texas 77075

P: 713.507.4251 • F: 713.507.4295

Email: [ri@reefindustries.com](mailto:ri@reefindustries.com)

