

ATG-2 is a woven polypropylene geotextile fabric with high tensile strength. Construction is a 30 x 20 weave.

## PHYSICAL PROPERTIES AND TYPICAL VALUES

PROPERTY	ASTM TEST METHOD	U.S. VALUE	METRIC VALUE
Weight	D-3776	39 LB/1000 FT <sup>2</sup>	19 KG/100 M <sup>2</sup>
Thickness	D-1777	17 MIL	0.43 MM
Abrasion Resistance Warp	D-1175	70 LBS	311 N
Grab Tensile	D-1682	270 LBS	1201 N
Trapezoidal Tear	D-2263	80 LBS	356 N
Burst Strength	D-751	535 LBS/IN <sup>2</sup>	3.7 MPA
Puncture Strength	D-4833	160 LBS	712 N
Air Flow	D-737	50 CFM	
Water Flow	D-4491	33 GAL/Min/Ft <sup>2</sup>	

## AVAILABLE COLORS

Black

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, expressed or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

©2006 REEF INDUSTRIES, INC. Armorlon is a registered trademark of Reef Industries, Inc. 09-06

**TOLLFREE 1.800.231.6074**

9209 Alameda Genoa Rd. • Houston, Texas 77075

P: 713.507.4251 • F: 713.507.4295

Email: [ri@reefindustries.com](mailto:ri@reefindustries.com)

