

Banner Guard® Standard conforms to the following safety codes:

OSHA 29 CFR Part 1910.144 - Safety Color Codes for Marking Physical Hazards

ANSI Z535.1 - Safety Color Codes

ISO 3864 - Safety Colours and Safety Signs

PHYSICAL PROPERTIES AND TYPICAL VALUES

| PROPERTY | ASTM TEST METHOD | U.S. VALUE | METRIC VALUE |
|-------------------|------------------|-------------------------------|---------------------------|
| Thickness Overall | D-2103 | 4.0 MIL | 0.1 MM |
| Weight | D-2103 | 18.5 LBS/1000 FT ² | 9.0 KG/100 M ² |
| 3" Tensile | D-882 | 34 LBF | 151 N |
| | | 2800 PSI | 19.3 MPA |
| Elongation | D-882 | 800 % | 800 % |
| PPT Resistance | D-2582 | 14 LBF | 62 N |
| Printability | D-2578 | ≥ 40 Dynes | ≥ 40 Dynes |

FEATURES

- Warn against hazardous areas by containing and alerting people of hazardous or restricted areas. Perfect for crime scenes, fire scenes, dangerous work areas, crowd control, open trenches, construction sites, wet floors, wet paint, overhead dangers, ski and race track boundaries, etc.
- Attention-getting message repeats warning continuously in bold black letters.
- Tough, durable and lightweight, yet strong enough to be used over and over again.
- Easy application and removal. Tape quickly wraps around poles, trees, and barrels; it can be stapled or nailed to posts, walls or barricades to establish a highly visible barrier with the appropriate message. Banner Guard® is the fast, effective way to identify and define areas with restricted entry.
- Made from reusable non-adhesive pigmented polyethylene. Manufactured for durability and resistance to the elements while being an environmentally friendly, heavy metal free product.
- The material is available in orange and yellow. Other colors may be available upon request.

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, expressed or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

