

**PHYSICAL PROPERTIES AND TYPICAL VALUES**

PROPERTY	ASTM TEST METHOD	U.S. VALUE	METRIC VALUE
Thickness Overall	D-2103	6.0 MIL	0.15 MM
Weight	D-2103	27.5 LBS/1000 FT <sup>2</sup>	13.4 KG/100 M <sup>2</sup>
3" Tensile	D-882	50.0 LBS	222 N
		2770 PSI	19.1 MPA
Elongation	D-882	1000 %	1000 %
PPT Resistance	D-2582	19 LBF	85 N
Printability	D-2578	≥ 40 Dynes	≥ 40 Dynes

**FEATURES**

- Terra Tape® Premium is a pigmented polyolefin film with a printed message on one side used to protect, identify and locate underground utility lines.
- The ink used to print the material is permanent and cannot be removed by normal handling or upon burial.
- The material and ink are chemically inert and will not degrade when exposed to acids, alkalis and other destructive substances commonly found in soil.
- The material is available in the colors orange, yellow and white. Other colors may be available upon request.

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, expressed or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

**TOLLFREE 1.800.231.6074**

9209 Alameda Genoa Rd. • Houston, Texas 77075

P: 713.507.4251 • F: 713.507.4295

Des de Mexico 001.800.426.1447

Email: [ri@reefindustries.com](mailto:ri@reefindustries.com)

